


NW6526CX1

650V Silicon Carbide Mosfet

Parameter	Value	Unit
V_{DS}	650	V
$R_{DS(on)}(V_{GS}=15V)$	260	$m\Omega$
$R_{DS(on)}(V_{GS}=18V)$	180	$m\Omega$
$I_D (T_C = 25^\circ C)$	17	A

Features

- High Speed Switching with Low Capacitances
- High Blocking Voltage with low on-resistance
- Low on-resistance with high junction temperaturel
- Fast intrinsic diode with low reverse recovery (Q_{rr})
- RoHS Compliant



Applications

- PC Power
- EV Charging
- LED Lighting
- Solar PV inverters / UPS
- Server Power / Telecom Power

Description

The NW6526CX1 is a 650 V, SiC mosfet based on NovaWave's advanced SiC technology resulting in high performance and long-term reliability. It supports high-temperature operation while showing minimal losses , zero reverse recovery, and low leakage current.

Part Description

Part Number	Package	Marking
NW6526CX1	TO252	NW6526CX1

Absolute Maximum Ratings

$T_J = 25^\circ\text{C}$ except as noted. Exceeding the maximum ratings may damage the device.

Gate-source transient voltage, $t_p < 1\ \mu\text{s}$, $t \leq 10$ hours over lifetime, $-10/+22\text{V}$

Parameter	Symbol	Value	Unit	Test conditions
Drain-Source Voltage	V_{DSmax}	650	V	$V_{GS} = 0\text{ V}$, $I_D = 100\ \mu\text{A}$
Continuous Drain Current, limited by $T_{j(max)}$	I_D	17	A	$V_{GS}=15\text{V}, T_C=25^\circ\text{C}$
		12		$V_{GS}=15\text{V}, T_C=100^\circ\text{C}$
Pulse Drain Current, Pulse width t_p limited by T_{jmax}	$I_{D(pulse)}$	25	A	$V_{GS} = 15\text{ V}$, $T_C = 25^\circ\text{C}$
Avalanche energy, single pulse	E_{AS}	25	mJ	$I_D = 10\text{A}$, $V_{DS} = 50\text{V}$, $L = 0.5\text{mH}$, $V_{GS} = 15\text{ V}$
Power Dissipation	P_D	67	W	$T_C=25^\circ\text{C}$
		33		$T_C=100^\circ\text{C}$
Recommended turn-on Gate Source Voltage	$V_{GS(on)}$	+15/+18	V	
Recommended turn-off Gate Source Voltage	$V_{GS(off)}$	-4/0	V	
Maximum Gate Source Voltage, transient voltage	V_{GSmax}	-10/+22	V	AC ($f > 1\text{ Hz}$)
Operating Junction and Storage Temperature Range	T_{VJ} , T_{stg}	-55/+175	$^\circ\text{C}$	
Soldering Temperature	T_L	260	$^\circ\text{C}$	

Thermal Characteristics

Parameter	Symbol	Min	Typ	Max	Unit
Thermal Resistance from Junction to Case	$R_{TH(J-C)}$		2.23		$^\circ\text{C/W}$

Electrical Characteristics

at $T_C = 25^\circ\text{C}$, unless otherwise specified

Parameters	Symbol	Min	Typ	Max	Unit	Condition
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	650	--	--	V	$I_D=100\mu\text{A}$, $V_{GS}=0\text{V}$

Parameters	Symbol	Min	Typ	Max	Unit	Condition
Zero Gate Voltage Drain Current	I_{DSS}	--	0.1	20	μA	$V_{DS}=650V, V_{GS}=0V, T_{VJ} = 25^{\circ}C$
		--	1	--		$V_{DS}=650V, V_{GS}=0V, T_{VJ} = 175^{\circ}C$
Gate-Source Leakage Current	I_{GSS}	--	--	250	nA	$V_{GS}=22V$
Gate Threshold Voltage	$V_{GS(th)}$	--	4.2	--	V	$V_{DS}=V_{GS}, I_D=10mA, T_J=25^{\circ}C$
		--	2.9	--		$V_{DS}=V_{GS}, I_D=10mA, T_J=175^{\circ}C$
Drain-Source On-State Resistance	$R_{DS(on)}$	--	260 230	--	m Ω	$V_{GS}=15V, I_D=5A, T_J=25^{\circ}C$ $T_J=175^{\circ}C$
		--	180 205	--	m Ω	$V_{GS}=18V, I_D=5A, T_J=25^{\circ}C$ $T_J=175^{\circ}C$
Forward Transconductance	g_{fs}	--	3.6	--	S	$V_{DS}=20V, I_D=5A$
Input Capacitance	C_{iss}	--	298	--	pF	$V_{DS}=650V, f=1MHz,$ $V_{GS}=0V, V_{AC}=25mV$
Output Capacitance	C_{oss}	--	27	--		
Reverse Transfer Capacitance	C_{rss}	--	4	--		
Internal Gate Resistance	$R_{G(int)}$	--	25	--	Ω	$f=1MHz, V_{AC}=25mV$
Total Gate Charge	Q_g	--	12.5	--	nC	$V_{DS}=400V, I_D=5A, V_{GS}=0/+15V$
Gate to Source Charge	Q_{gs}	--	4.1	--		
Gate to Drain Charge	Q_{gd}	--	1.7	--		

Turn-On Delay Time	$t_{d(on)}$	--	6.4	--	ns	$V_{DD}=400V$, $I_D=5A$, $V_{GS}=0V/+15V$, $R_{G(on)}=2.2\Omega$, $R_{G(off)}=2.2\Omega$ $L=600\mu H$, $T_{VJ}=25^{\circ}C$ FWD = Body Diode
Rise Time	t_r	--	18.1	--		
Turn-Off Delay Time	$t_{d(off)}$	--	17.5	--		
Fall Time	t_f	--	32	--		
Turn-On Energy	E_{on}	--	43	--	μJ	
Turn-Off Energy	E_{off}	--	5.4	--		
Total switching Energy	E_{Total}	--	48.4	--		
Turn-On Delay Time	$t_{d(on)}$	--	5.9	--	ns	$V_{DD}=400V$, $I_D=5A$, $V_{GS}=0V/+15V$, $R_{G(on)}=2.2\Omega$, $R_{G(off)}=2.2\Omega$ $L=600\mu H$, $T_{VJ}=175^{\circ}C$ FWD = Body Diode
Rise Time	t_r	--	14.1	--		
Turn-Off Delay Time	$t_{d(off)}$	--	21.1	--		
Fall Time	t_f	--	35.3	--		
Turn-On Energy	E_{on}	--	40.5	--	μJ	
Turn-Off Energy	E_{off}	--	5.1	--		
Total switching Energy	E_{Total}	--	45.6	--		

Reverse Diode Characteristics

Parameters	Symbol	Min	Typ	Max	Unit	Condition
Diode Forward Voltage	V_{SD}		3.1 2.7		V	$V_{GS}=0V, I_S=2.5A, T_{VJ}=25^{\circ}C$ $T_{VJ}=175^{\circ}C$
Continuous Diode Forward Current	I_S	--	17	--	A	$V_{GS}=-4V$
Diode pulse Current	$I_{S(pulse)}$	--	25	--	A	Pulse width t_p , limited by T_{jmax}
Reverse Recovery Time	t_{rr}		9.7		ns	$V_{GS}=0V, I_S=4A,$ $V_{DS}=400V,$ $di/dt=1.2A/ns,$ $T_{VJ}=25^{\circ}C$
Reverse Recovery Charge	Q_{rr}		32.4		nC	
Peak Reverse Recovery Current	I_{rrm}		5.6		A	
Reverse Recovery Time	t_{rr}		9.2		ns	$V_{GS}=0V, I_S=4A,$ $V_{DS}=400V,$ $di/dt=1.2A/ns,$ $T_{VJ}=175^{\circ}C$
Reverse Recovery Charge	Q_{rr}		36		nC	
Peak Reverse Recovery Current	I_{rrm}		6.1		A	

Electrical Performance Graphs




Figure 1. Typical Output Characteristics
 $T_j = -55^{\circ}\text{C}$




Figure 2. Typical Output Characteristics
 $T_j = 25^{\circ}\text{C}$




Figure 3. Typical Output Characteristics
 $T_j = 175^{\circ}\text{C}$




Figure 4. On-Resistance vs. Drain Current for Various Temperature




Figure 5. On-Resistance vs. Temperature for Various Gate Voltage




Figure 6. On-Resistance vs. Gate Voltage for Various Junction Temperature




Figure 7. Typical Transfer Characteristic for Various Temperatures




Figure 8. Typical 3rd Quadrant Characteristics at $T_J = -55\text{ }^{\circ}\text{C}$




Figure 9. Typical 3rd Quadrant Characteristics at $T_j = 25^\circ\text{C}$




Figure 10. Typical 3rd Quadrant Characteristics at $T_j = 125^\circ\text{C}$




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristics




Figure 13. Typical Capacitances vs. Drain-Source Voltage (0 – 650V)




Figure 14. Continuous Drain Current Derating vs. Case Temperature




Figure 15. Maximum Power Dissipation Derating vs. Case Temperature




Figure 16. Transient Thermal Impedance (Junction-Case) with different duty cycle




Figure 17. Clamped Inductive Switching Energy vs. Drain Current




Figure 18. Clamped Inductive Switching Energy vs. Junction Temperature




Figure 19. Clamped Inductive Switching Energy vs. R_g




Figure 20. Safe Operating Area

Testing conditions




Figure A: Definition of Q_{gd}




Figure B: Definition of switching times




Figure C: Definition of switching losses





Figure D: Definition of reverse recovery

Package Dimensions



SYMBOL	Unit(mm)			SYMBOL	Unit(mm)		
	MIN	NOM	MAX		MIN	NOM	MAX
A	2.20	2.30	2.38	E1	4.70	--	--
A1	0.00	--	0.10	e	2.186	2.286	2.386
A2	0.90	1.01	1.10	H	9.80	10.10	10.40
b	0.72	--	0.85	L	1.40	1.50	1.70
b1	0.71	0.76	0.81	L1	2.90 REF		
b2	0.72	--	0.90	L2	0.50 BSC		
b3	5.13	5.33	5.46	L3	0.90	--	1.25
c	0.47	--	0.60	L4	0.60	0.80	1.00
c1	0.46	0.51	0.56	L5	0.15	--	0.75
c2	0.47	--	0.60	L6	1.80 REF		
D	6.00	6.10	6.20	θ	0°	--	8°
D1	5.25	--	--	θ1	5°	7°	9°
E	6.50	6.60	6.70	θ2	5°	7°	9°



Disclaimer

The information given in this document is intended as a reference only and shall not in any event be regarded as a guarantee of performance. Novawave does not assume any liability arising out of the use of any product described herein, including but not limited to any personal injury, death, or property or environmental damage. The products shown herein are not designed for use as critical components in medical, life-saving, or life-sustaining applications, whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness. No licenses, patent rights, or any other intellectual property rights is granted or conveyed. Novawave reserves the right to make changes without further notice to any products herein to improve reliability, function, or design. Novawave standard terms and conditions apply. All rights reserved.